

# **Carefree Emulsion**

#### Description

**Carefree Emulsion** is a metallised dry bright floor polish which gives a long lasting gloss finish. **Carefree Emulsion** not only protects and extends the life of floors but also provides a safe high gloss finish which is easy to maintain and resistant to scuffing

#### **Key properties**

Unique triple polymer technology from Johnson Diversey 18 % solids Optimal blend of polymers, waxes resins and film formation ingredients. Provides a slip resistant finish.

#### **Benefits**

- Produces a hard wearing durable floor finish
- Acts as a sacrificial wear layer for resilient and hard floor coverings
- Good level of gloss
- Excellent resistance to scuffs and marks

#### **Use instructions**

Ensure old polish is removed

Apply only to a clean dry floor

Post Wet floor signs

Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out, the mop or applicator should be saturated but not dripping

Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.

Allow 20-30 minutes drying time. Ensure  $1^{st}$  coat is completely dry before applying a second coat, at right angles to the first coat applying product up to the edges. If required apply a  $3^{rd}$  coat in a similar manner.

Some floors such as stone, or worn porous/ vinyl will require sealing with Carefree Undercoat prior to application of **Carefree Emulsion**.

Regularly maintain the floor by damp mopping, machine scrubbing or spray cleaning. The ideal maintenance product for **Carefree Emulsion** is Carefree Maintainer.

#### **Technical data**

Appearance:	Milky emulsion
pH neat	8.0 - 9.0
pH Diluted	Not applicable
S.G.	1.03
Viscosity	Water thin

The above data is typical of normal production and should not be taken as a specification.





# **Carefree Emulsion**

## Safe handling and storage information

Store in original closed containers away from extreme temperatures. Keep from freezing Do not use at temperatures below 10 ° C

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

### **Product compatibility**

Suitable for use on vinyl, thermoplastic, rubber, linoleum, marble and terrazzo, it may also be used on sealed wood and cork floors.

#### Available pack sizes

2 x 5 L

JohnsonDiversey (UK) Weston Favell Centre Northampton NN3 8PD Tel. 0800 525 525 www.johnsondiversey.com P01325GBEN-02